JioLux

LIGHTING, ENGINEERED WITH ELEGANCE

TECHNICAL DATASHEET

JL-WL-1013

Wall & Decorative Hospitality

COB Surface & Pendant Light - 25W 3000K IP44

Surface & Pendant Light | Suspended / Pendant | IP44 | 3-Year Warranty



ARCHITECTURAL OVERVIEW

The ST-SL-25W-R80 is a high-intensity cylindrical surface spotlight designed for high-ceiling applications and bold architectural accents. Driven by a premium COB chip and a precision 36 deg optic, it delivers a powerful

POWER **25W**	LUMINOUS FLUX **2,650 lm**
COLOR TEMP **3000K**	PROTECTION **IP44**
CRI / OPTICS **36 deg**	WARRANTY **3 Years**

TECHNICAL SPECIFICATIONS

Model / SKU	JL-WL-1013	**Ingress Protection**	IP44
Collection	Wall & Decorative Hospitality	**Input Voltage & Freq.**	220-240V AC | 50/60Hz
Power Consumption	25W	**Dimming / Control**	On/Off (DALI-2 Optional)
Luminous Output	2,650 lm	**Mounting Type**	Suspended / Pendant
System Efficacy	106 lm/W	**Housing & Finish**	Die-cast Aluminum - Matte White
Color Temperature (CCT)	3000K	**Dimensions (mm)**	80-180mm
Color Rendering Index	Ra >=90	**Cut-Out Size (mm)**	N/A
Beam Angle / Optics	36 deg	**Rated Lifespan & Warranty**	50,000 Hrs (L70) | 3 Years

PROJECT SPECIFICATION & ENGINEERING SUPPORT

Custom CCT, DALI-2 / Casambi dimming, emergency battery kits, and DIALux photometric files (IES/LDT) are available on project request.