JioLux

LIGHTING, ENGINEERED WITH ELEGANCE

TECHNICAL DATASHEET

JL-WL-1012

Wall & Decorative Hospitality

SMD Pathway Light - 1-9W IP68

Pathway Light | Architectural Mount | IP68 | 3-Year Warranty



ARCHITECTURAL OVERVIEW

This corner lighting unit (TDQJ A Gr, 1-3W) features a compact grey housing designed for subtle architectural accents. Its construction includes SKD components with a glass front, rubber sealing, screws, and protective

POWER **1-9W**	LUMINOUS FLUX **110-990 lm**
COLOR TEMP **3000K / 4000K**	PROTECTION **IP68**
CRI / OPTICS **15 deg / 24 deg / 36 deg**	WARRANTY **3 Years**

TECHNICAL SPECIFICATIONS

Model / SKU	JL-WL-1012	**Ingress Protection**	IP68
Collection	Wall & Decorative Hospitality	**Input Voltage & Freq.**	220-240V AC | 50/60Hz
Power Consumption	1-9W	**Dimming / Control**	On/Off (DALI-2 Optional)
Luminous Output	110-990 lm	**Mounting Type**	Architectural Mount
System Efficacy	110 lm/W	**Housing & Finish**	Die-cast Aluminum - Anodized Sil
Color Temperature (CCT)	3000K / 4000K	**Dimensions (mm)**	35-85-85mm
Color Rendering Index	Ra >=90	**Cut-Out Size (mm)**	N/A
Beam Angle / Optics	15 deg / 24 deg / 36 deg / 60 de	**Rated Lifespan & Warranty**	50,000 Hrs (L70) | 3 Years

PROJECT SPECIFICATION & ENGINEERING SUPPORT

Custom CCT, DALI-2 / Casambi dimming, emergency battery kits, and DIALux photometric files (IES/LDT) are available on project request.