JioLux

LIGHTING, ENGINEERED WITH ELEGANCE

TECHNICAL DATASHEET

**JL-WL-1012**

Wall & Decorative Hospitality

# SMD Pathway Light - 1-9W IP68

**Pathway Light | Architectural Mount | IP68 | 3-Year Warranty**



## ARCHITECTURAL OVERVIEW

This corner lighting unit (TDQJ A Gr, 1-3W) features a compact grey housing designed for subtle architectural accents. Its construction includes SKD components with a glass front, rubber sealing, screws, and protective

| | |
|---|---|
| POWER<br>**1-9W** | LUMINOUS FLUX<br>**110-990 lm** |
| COLOR TEMP<br>**3000K / 4000K** | PROTECTION<br>**IP68** |
| CRI / OPTICS<br>**15 deg / 24 deg / 36 deg** | WARRANTY<br>**3 Years** |

## TECHNICAL SPECIFICATIONS

| | | | |
|---|---|---|---|
| **Model / SKU** | JL-WL-1012 | **Ingress Protection** | IP68 |
| **Collection** | Wall & Decorative Hospitality | **Input Voltage & Freq.** | 220-240V AC \| 50/60Hz |
| **Power Consumption** | 1-9W | **Dimming / Control** | On/Off (DALI-2 Optional) |
| **Luminous Output** | 110-990 lm | **Mounting Type** | Architectural Mount |
| **System Efficacy** | 110 lm/W | **Housing & Finish** | Die-cast Aluminum - Anodized Sil |
| **Color Temperature (CCT)** | 3000K / 4000K | **Dimensions (mm)** | 35-85-85mm |
| **Color Rendering Index** | Ra >=90 | **Cut-Out Size (mm)** | N/A |
| **Beam Angle / Optics** | 15 deg / 24 deg / 36 deg / 60 de | **Rated Lifespan & Warranty** | 50,000 Hrs (L70) \| 3 Years |

### PROJECT SPECIFICATION & ENGINEERING SUPPORT

Custom CCT, DALI-2 / Casambi dimming, emergency battery kits, and DIALux photometric files (IES/LDT) are available on project request.