JioLux

LIGHTING, ENGINEERED WITH ELEGANCE

TECHNICAL DATASHEET

JL-PD-1002

Chandeliers & Pendants

SMD Surface Light - 17W 3000K

Surface Light | Surface Mounted | IP20 | 3-Year Warranty



ARCHITECTURAL OVERVIEW

The ST-DS-17W-R350 is a professional wide-aperture surface luminaire designed for uniform ambient lighting. Featuring a high-performance SMD module and a 110 deg wide-beam acrylic diffuser, it delivers a soft,

POWER **17W**	LUMINOUS FLUX **1,870 lm**
COLOR TEMP **3000K**	PROTECTION **IP20**
CRI / OPTICS **110 deg**	WARRANTY **3 Years**

TECHNICAL SPECIFICATIONS

Model / SKU	JL-PD-1002	**Ingress Protection**	IP20
Collection	Chandeliers & Pendants	**Input Voltage & Freq.**	220-240V AC | 50/60Hz
Power Consumption	17W	**Dimming / Control**	On/Off (DALI-2 Optional)
Luminous Output	1,870 lm	**Mounting Type**	Surface Mounted
System Efficacy	110 lm/W	**Housing & Finish**	Die-cast Aluminum - Matte White
Color Temperature (CCT)	3000K	**Dimensions (mm)**	120-350mm
Color Rendering Index	Ra >=90	**Cut-Out Size (mm)**	N/A
Beam Angle / Optics	110 deg	**Rated Lifespan & Warranty**	50,000 Hrs (L70) | 3 Years

PROJECT SPECIFICATION & ENGINEERING SUPPORT

Custom CCT, DALI-2 / Casambi dimming, emergency battery kits, and DIALux photometric files (IES/LDT) are available on project request.