JioLux

LIGHTING, ENGINEERED WITH ELEGANCE

TECHNICAL DATASHEET

JL-PD-1025

Chandeliers & Pendants

SMD Surface & Pendant Light - 12W

Surface & Pendant Light | Suspended / Pendant | IP20 | 3-Year Warranty



ARCHITECTURAL OVERVIEW

The ST-SL-12W-L138 is a professional-grade surface-mounted spotlight designed for precise architectural highlighting. Housed in a premium die-cast aluminum body with a durable powder-coated finish, it utilizes high-power SMD

POWER **12W**	LUMINOUS FLUX **1,320 lm**
COLOR TEMP **3000K / 4000K**	PROTECTION **IP20**
CRI / OPTICS **15 deg**	WARRANTY **3 Years**

TECHNICAL SPECIFICATIONS

Model / SKU	JL-PD-1025	**Ingress Protection**	IP20
Collection	Chandeliers & Pendants	**Input Voltage & Freq.**	220-240V AC | 50/60Hz
Power Consumption	12W	**Dimming / Control**	On/Off (DALI-2 Optional)
Luminous Output	1,320 lm	**Mounting Type**	Suspended / Pendant
System Efficacy	110 lm/W	**Housing & Finish**	Die-cast Aluminum - Matte White
Color Temperature (CCT)	3000K / 4000K	**Dimensions (mm)**	138-35-83mm
Color Rendering Index	Ra >=90	**Cut-Out Size (mm)**	N/A
Beam Angle / Optics	15 deg	**Rated Lifespan & Warranty**	50,000 Hrs (L70) | 3 Years

PROJECT SPECIFICATION & ENGINEERING SUPPORT

Custom CCT, DALI-2 / Casambi dimming, emergency battery kits, and DIALux photometric files (IES/LDT) are available on project request.