JioLux

LIGHTING, ENGINEERED WITH ELEGANCE

TECHNICAL DATASHEET

JL-PD-1003

Chandeliers & Pendants

SMD Surface & Pendant Light - 15W

Surface & Pendant Light | Suspended / Pendant | IP20 | 3-Year Warranty



ARCHITECTURAL OVERVIEW

This track mounted SKD unit is supplied without an LED chip or driver, allowing full customization of the light engine. All structural and mechanical components are included, providing a complete housing solution.

POWER **15W**	LUMINOUS FLUX **770-1,650 lm**
COLOR TEMP **3000K / 4000K**	PROTECTION **IP20**
CRI / OPTICS **38 deg**	WARRANTY **3 Years**

TECHNICAL SPECIFICATIONS

Model / SKU	JL-PD-1003	**Ingress Protection**	IP20
Collection	Chandeliers & Pendants	**Input Voltage & Freq.**	220-240V AC | 50/60Hz
Power Consumption	15W	**Dimming / Control**	On/Off (DALI-2 Optional)
Luminous Output	770-1,650 lm	**Mounting Type**	Suspended / Pendant
System Efficacy	51 lm/W	**Housing & Finish**	Die-cast Aluminum - Matte White
Color Temperature (CCT)	3000K / 4000K	**Dimensions (mm)**	52-98-130mm
Color Rendering Index	Ra >=90	**Cut-Out Size (mm)**	N/A
Beam Angle / Optics	38 deg	**Rated Lifespan & Warranty**	50,000 Hrs (L70) | 3 Years

PROJECT SPECIFICATION & ENGINEERING SUPPORT

Custom CCT, DALI-2 / Casambi dimming, emergency battery kits, and DIALux photometric files (IES/LDT) are available on project request.